



A versatile, highly portable pancake lens with STM and a fast maximum aperture

A versatile, compact pancake lens. A fast maximum aperture enables low-light shooting and depth-of-field control. STM provides smooth quiet autofocus when shooting video with compatible cameras.

The EF 40mm f/2.8 STM is part of the Canon EF range of standard lenses:

- EF 35mm f/2
- EF 40mm f/2.8 STM**
- EF 50mm f/1.2L USM
- EF 50mm f/1.4 USM
- EF 50mm f/1.8 II

**Sales Start Date:** June 2012  
**Target Market:** A portable, versatile lens with STM for photographers travelling with their EOS

Key Features:

- The compact pancake design of the EF 40mm f/2.8 STM makes your EOS even more portable, so you'll always be able to take your DSLR with you.
- Movie Servo AF uses STM stepping-motor technology for smooth quiet focusing when shooting video with compatible cameras.
- Use an f/2.8-22 aperture range to control depth of field and shoot hand-held in low-light conditions. A circular aperture diaphragm delivers high-quality bokeh.
- Suitable for a wide variety of subjects, from portraits to landscapes. Great for discreet reportage photography.
- Pin-sharp images with fast, quiet AF with STM.
- Great image quality right across the frame with Super Spectra Coatings and aspherical lens design.

Product Name	Mercury Code	EAN Code	Recommended Retail Price
EF 40mm f/2.8 STM	6310B005AA	4690999845715	£229.99 / €279.99
What's in the box: EF 40mm f/2.8 STM lens, Lens cap E-52, Lens dust cap E, Instruction book, Warranty card			

Accessories	Mercury Code	EAN Code
Lens Hood ES-52	5182B001AA	4960999780627
Lens case/pouch LP811	2784A001BA	4960999470788

## Technical Specifications

# EF 40mm f/2.8 STM

<b>OPTICAL FEATURES / SPECIFICATIONS</b> Image size 35mm film equivalent focal length (mm) Angle of view Horizontal Vertical Diagonal Lens construction (elements / groups) No. of diaphragm blades Minimum aperture Closest focusing distance (m) Maximum magnification (x) Distance information Image stabilizer AF actuator	- - 49° 34° 57° 6 / 4 7 22 0.3 0.18 None - STM
<b>PHYSICAL SPECIFICATIONS</b> Dust / moisture resistance <sup>[4]</sup> Filter diameter (mm) Maximum diameter x length (mm) Weight (g)	- 52 68.2 x 22.8 130
<b>ACCESSORIES</b> Lens cap Lens hood Lens case / pouch Maximum number of Hood III compatible with Gelatin Filter Holder III Maximum number of Hood IV compatible with Gelatin Filter Holder IV Magnification with Extension Tube EF12 II Magnification with Extension Tube EF25 II Extender compatibility Other accessories	E-52 EW-52 LP811 - - 0.50-0.32 0.88-0.70 Not compatible -

All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated. Subject to change without notice.

[3] Full time manual focus.

[4] Lenses with dust / moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.

[5] Not compatible at wide angles.

## Logistics Information

Pack Description	Quantity	Dimensions (L x W x H in mm)	Weight (Net / Gross in kg)
Individual	1	110 x 110 x 118	145g / 256.5g
Outer	30	573 x 351 x 285	7.7 / 8.86
Pallet	360		

