



EF 70-300mm f/4-5.6L IS USM
Specification Sheet

Optical Features/Specifications

	Angle of view (horizontal, vertical, diagonal)	29° - 6° 50', 19° 30' - 4° 35', 34° - 8° 15'
	Lens construction (elements/groups)	19/14
	No. of diaphragm blades	8
	Minimum aperture	32-45
	Closest focussing distance (m)	1.2
	Maximum magnification (x)	0.21 (at 300mm)
	Distance Information	Provided
	Image stabilizer	4-stops
	AF actuator	Ring USM ³

Physical Specifications

	Dust/moisture resistance ⁴	Yes
	Filter diameter (mm)	67
	Max. diameter x length (mm)	89 x 143
	Weight (g)	1050

Accessories

	Lens Cap	E-67U
	Lens hood	ET-73B
	Lens case/pouch	LP1424
	Maximum number of Hood III compatible with Gelatin Filter Holder III	3
	Maximum number of Hood IV compatible with Gelatin Filter Holder IV	3
	Magnification with Extension Tube EF12 II	0.29-0.04
	Magnification with Extension Tube EF25 II	0.38-0.09
	Extender Compatibility	NC
	Other Accessories	Ring type tripod mount C (WII)

All data is based on Canon standard testing methods except where indicated.
Subject to change without notice.

³ Full time Manual focus

⁴ Lenses with dust/moisture resistance are fitted with a rubber ring on the lens mount which may cause slight abrasion of the camera mount. This in no way effects either the lens or camera performance.