		SPEEDLITE 430EX III-RT
Power	Cuida Na (ICO100) madam	10 (205
7	Guide No. (ISO100).meters	43 (105mm)
Zoom	7.0000 h 0 000	Yes
	Zoom head focal length coverage	24-105mm
	Coverage with wide panel	14mm
	Auto zoom for sensor size	Yes
	AUTO ZOOTTI TOI SETISOI SIZE	res
Flash modes	Auto exposure control	E-TTLII/E-TTL
	High speed sync (FP)	Yes
	Manual / output settings	Yes - 1/1- 1/128
	Manual steps	1/3 step
	Strobe / output settings	
	Frequency	_
	Video light	_
	Video light power	
	Video light colour temperature	_
Flash-related function	rideo ligiti coloui lettipelatule	-
nush-related function	FE lock	Yes
	Flash exposure compensation	Yes
	Flash Exposure bracketing	No
	Second-curtain flash sync	Yes
	Modelling flash	Yes
	Colour temperature info communication	Yes
Wireless flash	Colodi lemperatore il ilo continto il callon	163
Wireless flasti	Transmitter	Yes
	Transmission type	Radio
	панзинзэни турс	Indoors: 12-15m / 30m
	Signal range (Infra-red/Radio)	Outdoors: 8-10m / 30m
	Slave function	Infra-red/Radio
	Master function	Radio
	No of groups (Optical/Radio)	- / 5
	No of channels (Optical/Radio)	- / 15
	Remote Shutter Release	Yes
Flash head movement	Kernete sherier kelease	103
Trasifficaa filoveitietii	Up	45, 60, 75 and 90°
	Down	-
	Left	60, 75, 90, 120, and 150°
	Right	60, 75, 90, 120, 150 and 180 °
AF Assist	Ngn	60, 73, 70, 120, 130 drid 180
VI V22121	AF-assist beam	Yes
	Number of AF points supported	1
	AF-assist beam type (centre AF point/other AF	•
	points)	Infra-red / flash strobe
Power source	p 0 moj	3 103 / 11311311000
1 0 1 0 0 0 0 0	Battery	4 x AA batteries
	Minimum recycling time *2	Approx. 3.5 sec
	External power supply	No
Construction		
- CONSTITUTION	Dust and water resistance	No
	Mounting foot material	Metal
Misc.		
	Custom function	10 (8 personal functions)
	Flash settings from camera menus *3	Yes
	External flash exposure sensor	No
	PC terminal	No
		Off-camera shoe cord OC-E3
		Bounce adapter SBA-E2
		Color filter/Bounce adapter
		holder
	Compatible Accessories	Color filter SCF-E2
I	1	

	Dedicated flash bracket	No
Dimensions & weight		
	Size (W x H x D), mm	70.5 x 113.8 x 98.2
	Weight (Excluding batteries), grams	295g
	Operating environment	
	Working temperature range:	0°C - 45°C / 32°F - 113°F
	Working humidity:	85 % or less

All data is based on Canon standard testing methods (according to CIPA Standards) except where indicated. Subject to change without notice.

[2] time taken to recharge flash after full discharge using Alkaline AA batteries [3] With compatible cameras only