

TECHNICAL BULLETIN Replaces Bulletin Dated: February 2004

Bulletin Number: TB819034 Effective March 2010:

Super Conditioning Tablets (FSC 100) For Processing C-41 and Compatible Color Negative Films & For Processing Fujicolor CA Papers and Process RA-4 Color Papers



Catalog Number: 60001311 (5 L x 100/Bottle)

DESCRIPTION

These tablets are designed to aid in the washing of film and paper emulsions in Fuji minilab equipment.

SAFE HANDLING INSTRUCTIONS

Please refer to Material Safety Data Sheets (MSDS) for specific chemical details. For emergencies, please contact CHEMTREC at 1-800-424-9300. You can obtain an MSDS by calling the Fujifilm Technical Hotline at 1-800-526-0851 Ext. 10.

HMIS INFORMATION

Hazardous Materials Identification System. Please refer to Section 3 in the MSDS for further information

	Tablets	Replenisher & Working Tank	
Health	1	0	
Flammability	0	0	
Reactivity	0	0	
Personal Protection	С	В	

MIXING INSTRUCTIONS – REPLENISHER & WORKING TANK

R&W	Water 95°– 105° F (35° – 41° C)	Add FSC 100 Tablet(s)
10 Liters	10 L	2 Tablets - Crushed
5 Liters	5 L	1 Tablet – Crushed

To Make 10 Liters:

- Start with 10 Liters of warm water.
- Add 2 crushed tablets.
- Mix 20 times or until tablets are dissolved.

SPECS & RECOMMENDATIONS/FILM CN-16Q

011 100		
Temperature	32° – 38° C	
remperature	90° – 100⊠ F	
Processing Time	1'40" (two tanks	
Starting	135-24	
Replenishment	30 ml/roll	
Rate	27 ml/m	

CN-16FA

Temperature	35° – 41° C	
remperature	95° – 105° F	
Processing Time	50" (two tanks)	
Starting	135-24	APS-25
Replenishment	34 ml/roll	19 ml/roll
Rate	30.6 ml/m	17.1 ml/roll

CN-16L

Tomporoture	35° – 41° C	
Temperature	95° – 105° F	
Processing Time	30" (one tank)	
Starting	135-24	APS-25
Replenishment	17 ml/roll	9.5 ml/roll
Rate	15.3 ml/m	8.55 ml/roll

SPECS & RECOMMENDATIONS/PAPER CP-471

01 -41 E		
Temperature	35° – 40° C	
· · · · · · · · · · · · · · · · · · ·	95° – 104° F	
Processing Time	1'30" (three tanks – FA Series or	
	four tanks – Super FA Series)	
Starting Replenishment Rate	With RC30/50	Without RC30/50
	121 ml/m²	242 ml/m²

CP-48S

Temperature	35° – 40° C 95° – 104° F	
Processing Time	1'30" (four tanks)	
Starting Replenishment Rate	With RC-50	Without RC-50
	121 ml/m²	175 ml/m²

SHELF LIFE

	Tablets	Replenisher	Working Tank
Time	U = 24 Months O = 24 Months	4 Weeks	2 Weeks
Color	White Tablets	Clear, Colorless	Clear, Colorless
Odor	Slight Chlorine Odor	Slight Chlorine Odor	Slight Chlorine Odor

U = Unopened, O = Opened

The data contained in this photographic bulletin is believed to be true and accurate, but is offered solely for your consideration, investigation, and verification. Nothing herein shall be construed to be a warranty or guarantee by either FUJIFILM Hunt Chemicals or any of its affiliates, and all such warranties, implied or otherwise, including any implied warranty of merchantability, are hereby expressly disclaimed. You, of course, are fully responsible for any use and / or domestic or foreign sale of the product(s) described, and nothing in this photographic bulletin shall be construed to constitute permission or a recommendation to practice any invention covered by patent or patent application or know-how owned by FUJIFILM, its affiliates, or others.